



National Aeronautics and
Space Administration

MSFC-STD-561
REVISION B
NOVEMBER 18, 2004

George C. Marshall Space Flight Center
Marshall Space Flight Center, Alabama 35812

EI11

**MULTIPROGRAM/PROJECT COMMON-USE
DOCUMENT**

**THREADED FASTENERS,
REQUIREMENTS FOR SECURING OF
FLIGHT HARDWARE USED ON
SHUTTLE PAYLOADS AND
EXPERIMENTS**

Approved for Public Release; Distribution Unlimited

**CHECK THE MASTER LIST—
VERIFY THAT THIS IS THE CORRECT VERSION BEFORE USE**

| | | |
|---|-----------------------------------|--------------------|
| Multiprogram/Project Common-Use Document EI11 | | |
| Title: Threaded Fasteners, Requirements for Securing of Flight Hardware used on Shuttle Payloads and Experiments | Document No.: MSFC-STD-561 | Revision: B |
| | Effective Date: 11/18/04 | Page 2 of 6 |

DOCUMENT HISTORY LOG

| Status (Baseline/ Revision/ Canceled) | Document Revision | Effective Date | Description |
|--|----------------------|-------------------|---|
| Baseline | -- | -- | Baseline Release |
| Revision | A | 2/01/1995 | Revision "A" replaces baseline release in its entirety. |
| Revision | B | 11/18/2004 | Revision "B" completed due to Center Rules Review. |
| | | | |

CHECK THE MASTER LIST VERIFY THAT THIS IS THE CORRECT VERSION BEFORE USE

| | | |
|---|-----------------------------------|--------------------|
| Multiprogram/Project Common-Use Document EI11 | | |
| Title: Threaded Fasteners, Requirements for Securing of Flight Hardware used on Shuttle Payloads and Experiments | Document No.: MSFC-STD-561 | Revision: B |
| | Effective Date: 11/18/04 | Page 3 of 6 |

FOREWORD

CONTENTS

| <u>PARAGRAPH</u> | | <u>PAGE</u> |
|------------------|------------------------------------|-------------|
| | <u>DOCUMENT HISTORY LOG</u> | 2 |
| | <u>FOREWORD</u> | 3 |
| 1. | <u>SCOPE</u> | 4 |
| 2. | <u>APPLICABLE DOCUMENTS</u> | 4 |
| 3. | <u>DEFINITIONS</u> | 4 |
| 4. | <u>GENERAL REQUIREMENTS</u> | 5 |
| 5. | <u>DETAILED REQUIREMENTS</u> | 5 |

1. SCOPE

CHECK THE MASTER LIST VERIFY THAT THIS IS THE CORRECT VERSION BEFORE USE

| Multiprogram/Project Common-Use Document EI11 | | |
|---|-----------------------------------|--------------------|
| Title: Threaded Fasteners, Requirements for Securing of Flight Hardware used on Shuttle Payloads and Experiments | Document No.: MSFC-STD-561 | Revision: B |
| | Effective Date: 11/18/04 | Page 4 of 6 |

- 1.1 This standard applies to Shuttle payloads (experiments, Mission Peculiar Equipment, etc.) for which MSFC has integration and or development responsibility. All structural and mechanical system hardware fasteners (NHB 1700.7) event.
- 1.2 Vibration testing has shown that thread fasteners may work loose and cause a hazard during actual flight conditions. This standard provides requirements and guidance for designers concerned with this potential problem.

2. APPLICABLE DOCUMENTS

- a. NASM33540 Safety Wiring and Cotter Pinning, General Practices for
- b. MSFC-STD-486 Threaded Fasteners, Torque Limits for
- c. NASM1312-7 Fastener Test Methods, Vibration
- d. NASA-STD-5003 Fracture Control Requirements for Payloads Using Space Transportation System
- e. NSTS 1700.7 Safety Policy and Requirements for Payloads Using the Space Transportation System
- f. NSTS 08307 Criteria for Preloaded bolts
- g. AS4536 Safety Cable Kit Procurement Specification and Requirements for use
- h. MWI 7120.4 Documentation Preparation, Programs/Projects
- i. MPR 7120.2 Multiprogram/Project Common-Use Documentation
- j. MSFC-SPEC-250 Protective Finishes for Space Vehicle Structures and Associated Flight Equipment
- k. MSFC-STD-506 Materials and Processes Control Standard
- l. MSFC-STD-2594 MSFC Fastener Management and Control Practices

CHECK THE MASTER LIST VERIFY THAT THIS IS THE CORRECT VERSION BEFORE USE

| | | |
|---|-----------------------------------|--------------------|
| Multiprogram/Project Common-Use Document EI11 | | |
| Title: Threaded Fasteners, Requirements for Securing of Flight Hardware used on Shuttle Payloads and Experiments | Document No.: MSFC-STD-561 | Revision: B |
| | Effective Date: 11/18/04 | Page 5 of 6 |

3. DEFINITIONS

Threaded fasteners are defined as screws, bolts, and nuts that are designed to be removed and reinstalled without functional damage to the fasteners. The cognizant engineering organization is defined as the activity which designs and produces end items for delivery to the government. The prime contractor shall be the cognizant engineering organization for sub-contractors and vendors. The prime contractor may delegate this responsibility to the sub-contractors or vendors.

4. GENERAL REQUIREMENTS

The cognizant engineering organization shall be responsible for application of good engineering practices to insure the safety of any fastener not specifically covered by the following requirements. The government reserves the right to inspect, test, and modify any fastener system when the potential for a catastrophic failure exists.

5. DETAILED REQUIREMENTS

- 5.1 All hardware designs shall utilize MSFC-STD-486 to establish the torque requirements, and these values shall be shown on the drawings. Design drawings shall specify which fasteners are to be safety wired, safety cabled, or cotter pinned. Safety wire, safety cable, cotter pins, and locking compounds shall be specified by part number on the drawing. Materials used for safety wire, safety cable, cotter pins shall comply with Table III of MSFC-SPEC-250. Safety wire and cotter pins shall be installed in accordance with MS33540; safety cable shall be installed in accordance with SAE Aerospace Standard AS 4536.
 - 5.1.1 Fracture critical threaded fasteners (per NHB 8071.1) shall be safety wired, safety cabled, or cotter pin to provide mechanical safing. Random vibration testing of the as used configuration shall not be used to justify a waiver to this requirement.
 - 5.1.2 Threaded fasteners used in application of retaining a rotating device (wheel and axle concept) shall be safety wired, safety cabled, or cotter pinned. Random vibration testing of the used configuration shall not be used to justify a waiver to this requirement.
 - 5.1.3 Redundant threaded fasteners (non fracture critical) shall employ safety wire, cotter pins, or self-locking threaded devices, or approved locking compounds. A Materials Usage Agreement (MUA) in accordance with (IAW) MSFC-STD-506 shall be submitted for all proposed locking compounds. Self-locking threaded devices shall meet MIL-STD-1312-7 or equivalent, as defined in the threaded fastener's standards procurement specification.
 - 5.1.4 Hardware which is designed for permanent installation shall use non-removable type fasteners, where possible. Designs for non-permanent installations (e.g., experiments or

CHECK THE MASTER LIST VERIFY THAT THIS IS THE CORRECT VERSION BEFORE USE

| | | |
|---|-----------------------------------|--------------------|
| Multiprogram/Project Common-Use Document EI11 | | |
| Title: Threaded Fasteners, Requirements for Securing of Flight Hardware used on Shuttle Payloads and Experiments | Document No.: MSFC-STD-561 | Revision: B |
| | Effective Date: 11/18/04 | Page 6 of 6 |

structural members that are changed for different flights) requiring the use of threaded fasteners shall avoid configurations that include inaccessible or difficult locations.

- 5.1.5 Exposed sharp ends of locking devices that could damage astronaut equipment or rupture lines during EVA shall be sealed with an approved compound. A MUA IAW MSFC-STD-506 shall be submitted for all proposed sealants.
- 5.1.6 Special precaution shall be exercised to preclude the possibility of mechanical equipment becoming jammed. When installing safety wire, safety cable, or cotter pins, cutoff remains shall be collected and properly discarded.
- 5.1.7 All hardware designs shall utilize the analysis methodology provided in NSTS08307. The procedure outlined in this document ensures that preloaded bolts have adequate strength and life, and that the joint itself will not experience separation.
- 5.1.8 Structural, fracture critical, and safety critical fasteners as defined by the program/project that are procured, received, tested, inventoried or installed for space flight by the Center or its contractors must meet the requirements of MSFC-STD-2594.

PACKAGE NO. 10443R

DOCUMENTATION RELEASE LIST
 GEORGE C. MARSHALL SPACE FLIGHT CENTER

MSFC CODE IDENT 14981/339B2
 ISSUE DATE FEB 22 2007

| C H | DOCUMENT NUMBER | DRL DRL DSH REV | TITLE | CCBD NO. | PCN | PC | EFFECTIVITY |
|----------------|--------------------|--------------------|---|-------------|---------|----|-------------|
| * MSFC-STD-561 | | 203 - | THREDED FASTENERS, SECURING OF FLIGHT HARDWARE USED ON SHUTTLE PAYLOADS AND EXPERIMENTS | 000-00-0000 | 0000000 | ZA | NONE |

| CHG NO. | CHG REV | CHG NOTICE | RESPONSIBLE ENGINEER | RESPONSIBLE ORGANIZATION | ACTION DATE | DESCRIPTION |
|------------|------------|---------------|-------------------------|-----------------------------|----------------|--|
| * 2 | S | DCN000 | EUGENA GOGGANS | EO03 | 02/22/07 | DOCUMENT RELEASED THRU PDS. NO LONGER TRACKED IN ICMS. |

CHECKER

N/A
 02/15/07

(FINAL)

PACKAGE NO: 10443R

PROGRAM/PROJECT: MULTI

LAST UPDATED: 02/22/07

NOMENCLATURE: MSFC-STD- GOING TO NONE EFFECTIVITY

| | | | |
|-----------|---------|----------------------------|----------------|
| ECR NO: | PCN: | CCBD NO: | DATE PREPARED: |
| EO03-0000 | 0000000 | 000-00-0000 SB3-00-0000 | 02/22/07 |

| DWG SIZE | DRAWING NUMBER | DWG REV | EPL/DRL/DDS NUMBER | DWG REV | EPL DSH | EPL REV | EO DASH NUMBER | EO REV | PART NUMBER |
|-------------|-------------------|------------|-----------------------|------------|------------|------------|-------------------|-----------|----------------|
| | | | MSFC-HDBK-1453 | | 202 | - | | | |
| | | | MSFC-HDBK-1674 | | 202 | - | | | |
| | | | MSFC-HDBK-2221 | | 203 | - | | | |
| | | | MSFC-HDBK-505 | | 202 | - | | | |
| | | | MSFC-HDBK-670 | | 202 | - | | | |
| | | | MSFC-MNL-1951 | | 209 | - | | | |
| | | | MSFC-PROC-1301 | | 202 | - | | | |
| | | | MSFC-PROC-1721 | | 202 | - | | | |
| | | | MSFC-PROC-1831 | | 202 | - | | | |
| | | | MSFC-PROC-1832 | | 202 | - | | | |
| | | | MSFC-PROC-404 | | 202 | - | | | |
| | | | MSFC-PROC-547 | | 202 | - | | | |
| | | | MSFC-QPL-1918 | | 204 | - | | | |
| | | | MSFC-RQMT-1282 | | 202 | - | | | |
| | | | MSFC-SPEC-1198 | | 202 | - | | | |
| | | | MSFC-SPEC-1238 | | 202 | - | | | |
| | | | MSFC-SPEC-1443 | | 202 | - | | | |
| | | | MSFC-SPEC-164 | | 202 | - | | | |
| | | | MSFC-SPEC-1870 | | 202 | - | | | |
| | | | MSFC-SPEC-1918 | | 203 | - | | | |
| | | | MSFC-SPEC-1919 | | 206 | - | | | |
| | | | MSFC-SPEC-2083 | | 202 | - | | | |
| | | | MSFC-SPEC-2223 | | 202 | - | | | |
| | | | MSFC-SPEC-2489 | | 206 | - | | | |
| | | | MSFC-SPEC-2490 | | 205 | - | | | |
| | | | MSFC-SPEC-2491 | | 203 | - | | | |
| | | | MSFC-SPEC-2492 | | 203 | - | | | |
| | | | MSFC-SPEC-2497 | | 211 | - | | | |
| | | | MSFC-SPEC-250 | | 202 | - | | | |
| | | | MSFC-SPEC-445 | | 202 | - | | | |
| | | | MSFC-SPEC-504 | | 202 | - | | | |
| | | | MSFC-SPEC-521 | | 202 | - | | | |
| | | | MSFC-SPEC-548 | | 202 | - | | | |
| | | | MSFC-SPEC-560 | | 202 | - | | | |
| | | | MSFC-SPEC-626 | | 202 | - | | | |
| | | | MSFC-SPEC-684 | | 202 | - | | | |
| | | | MSFC-SPEC-708 | | 202 | - | | | |
| | | | MSFC-SPEC-766 | | 202 | - | | | |
| | | | MSFC-STD-1249 | | 202 | - | | | |
| | | | MSFC-STD-1800 | | 202 | - | | | |
| | | | MSFC-STD-246 | | 202 | - | | | |
| | | | MSFC-STD-2594 | | 203 | - | | | |

PACKAGE NO: 10443R

| DWG SIZE | DRAWING NUMBER | DWG REV | EPL/DRL/DDS NUMBER | DWG REV | EPL DSH | EPL REV | EO DASH NUMBER | EO REV | PART NUMBER |
|-------------|-------------------|------------|-----------------------|------------|------------|------------|-------------------|-----------|----------------|
| | | | MSFC-STD-2903 | | 202 | - | | | |
| | | | MSFC-STD-2904 | | 202 | - | | | |
| | | | MSFC-STD-2905 | | 202 | - | | | |
| | | | MSFC-STD-2906 | | 202 | - | | | |
| | | | MSFC-STD-2907 | | 202 | - | | | |
| | | | MSFC-STD-366 | | 202 | - | | | |
| | | | MSFC-STD-383 | | 202 | - | | | |
| | | | MSFC-STD-486 | | 202 | - | | | |
| | | | MSFC-STD-506 | | 203 | - | | | |
| | | | MSFC-STD-531 | | 202 | - | | | |
| | | | MSFC-STD-557 | | 202 | - | | | |
| | | | MSFC-STD-561 | | 203 | - | | | |
| | | | MSFC-STD-781 | | 202 | - | | | |

| SUBMITTED BY ENGINEERING AREA: | BASIC | CHANGE | PARTIAL | COMPLETE | CLOSES | ACTION |
|--------------------------------|-------|--------|---------|----------|--------|--------|
| EO03 | | X | | X | | EO03 |

PREPARED BY:
EUGENA GOGGANS
12/19/06

SUBMITTED BY:

CONCURRENCE:

TRANSMITTAL DATES
TO RELEASE DESK 02/22/07 10:00
TO MSFC DOC REP 02/22/07 00:00

REMARKS:

2007 FEB 22 AM 11:22

MSFC DOCUMENTATION REPOSITORY - DOCUMENT INPUT RECORD

I. GENERAL INFORMATION

| | | | | |
|--|---|--------------------|--------------------------------|----------------------------------|
| 1. APPROVED PROJECT: Multiprogram Project | 2. DOCUMENT/DRAWING NUMBER: MSFC-STD-561 Rev B | 3. CONTROL NUMBER: | 4. RELEASE DATE: 11/18/2004 | 5. SUBMITTAL DATE: 11/30/2004 |
|--|---|--------------------|--------------------------------|----------------------------------|

| | |
|---|-----------------|
| 6. DOCUMENT/DRAWING TITLE: THREADED FASTENERS, REQUIREMENTS FOR SECURING OF FLIGHT HARDWARE USED ON SHUTTLE PAYLOADS AND EXPERIMENTS | 7. REPORT TYPE: |
|---|-----------------|

| | | |
|---|----------------|------------------------------|
| 8. CONTRACT NUMBER / PERFORMING ACTIVITY: | 9. DRD NUMBER: | 10. DPD / DRL / IDRD NUMBER: |
|---|----------------|------------------------------|

| | | |
|---|--------------------------|--------------------------|
| 11. DISPOSITION AUTHORITY (Check One): <input checked="" type="checkbox"/> Official Record - NRRS 8/11/A <input type="checkbox"/> Reference Copy - NRRS 8/5/A/3 (destroy when no longer needed) | 12. SUBMITTAL AUTHORITY: | 13. RELEASING AUTHORITY: |
|---|--------------------------|--------------------------|

14. SPECIAL INSTRUCTIONS:

| | |
|---|---|
| 15. CONTRACTOR/SUBMITTING ORGANIZATION, ADDRESS AND PHONE NUMBER: Andre Miller E11 Structural Design Branch MSFC, AI 35812 ph. 256-544-7014 | 16. ORIGINATING NASA CENTER: MSFC 17. OFFICE OF PRIMARY RESPONSIBILITY: E11 Structural Design Branch |
|---|---|

| | |
|---|----------------------|
| 18. PROGRAMMATIC CODE (5 DIGITS): 127-10-1E | 19. NUMBER OF PAGES: |
|---|----------------------|

II. ENGINEERING DRAWINGS

| | | | |
|---------------|------------------------|-----------------|-----------|
| 20. REVISION: | 21. ENGINEERING ORDER: | 22. PARTS LIST: | 23. CCBD: |
|---------------|------------------------|-----------------|-----------|

III. REPORTS, SPECIFICATIONS, ETC.

| | | | | | |
|---------------|---------------|-------------|--------------|----------------|--------------|
| 24. REVISION: | 25. CHANGE: | 26. VOLUME: | 27. BOOK: | 28. PART: | 29. SECTION: |
| 30. ISSUE: | 31. ANNEX: | 32. SCN: | 33. DCN: | 34. AMENDMENT: | |
| 35. APPENDIX: | 36. ADDENDUM: | 37. CCBD: | 38. CODE ID: | 39. IRN: | |

IV. EXPORT AND DISTRIBUTION RESTRICTIONS

| | |
|---|--|
| <input type="checkbox"/> Privacy Act (see MVA 1382.1) | <input type="checkbox"/> EAR (see MPG 2220.1) |
| <input type="checkbox"/> Proprietary (see MPD 2210.1) | <input type="checkbox"/> Other ACl (see NPG 1620.1 and MPG 1600.1) |
| <input type="checkbox"/> Patent (see MPG 2220.1) | <input checked="" type="checkbox"/> No statutory or institutional restrictions applicable -- material may be electronically distributed to user in the NASA domain |
| <input type="checkbox"/> ITAR (see MPG 2220.1) | |

V. ORIGINATING ORGANIZATION APPROVAL

| | | | |
|------------------------|-------------------------------------|---------------------------|---------------------------------|
| 40. ORG. CODE: ED23 | 41. PHONE NUMBER: (256) 544-7014 | 42. NAME: ANDRE MILLER | 43. SIGNATURE/DATE: 11/30/04 |
|------------------------|-------------------------------------|---------------------------|---------------------------------|

VI. TO BE COMPLETED BY MSFC DOCUMENTATION REPOSITORY

| | | |
|----------------------|-------------------------------|------------------------------|
| 44. RECEIVED BY: | 45. DATE RECEIVED: 12-6-04 | 46. WORK ORDER: 63-001005 |
|----------------------|-------------------------------|------------------------------|